

TEX WALK®

TexWalk® is a fabric with a textured matte vinyl coating. It is designed to be used for short to midterm applications, dependent on where the product is applied. TexWalk® works great on carpet, tile, concrete, wooden and PVC floors, untreated stone and almost every surface indoor and outdoor.

Durability

The durability of TexWalk® is dependent on the way the product has been applied and it also depends on the mechanical use of the surface where it is applied. Our experiences suggest the following:

- indoor floor up to 3 months (depending on traffic)
- outdoor sidewalk up to 3 months (depending on traffic)
- indoor wall up to 36 months
- outdoor wall up to 12 months

Life time can be significantly extended with EasyProtect liquid varnish.

Printing method

UV curable inks, solvent, ecosolvent and latex

Storage

Shelf life is 12 months from the date of delivery. Storage conditions +15°C to +24°C and relative humidity between 40% and 65%.

Waste handling

We recommend to handle the production waste and the used material as industrial waste.





Warranty

Continental Grafix products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the technical specification sheets. We will replace or refund the price of any Continental Grafix materials found to not meet our product specifications. In no case shall Continental Grafix be liable for any direct, indirect, or consequential damages, including labor or non-Continental Grafix materials charges. The determination of suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warrantees of any kind are made to the accuracy of suitability for specification.

Uses

- Applied on top of carpeting, tiles, wooden and PVC floors and untreated stone
- Wall graphics and door coverage
- Tradeshows (exhibition walls and floors)
- POP/POS

Features & Benefit

- Structured matte finish
- . No or almost no adhesive residue
- Sticks on almost any surface
- Easy to apply and remove
- Print and go no lamination solution
- Digital cutting into any shape

Technical Information		TexWalk
Size	Width: 1.22 m Length: 25.0 m, 50.00 m	
Material	Fabric with a textured matte vinyl coating (white)	0.10 - 0.25 mm
Adhesive	Permanent acrylic solvent	80μ +/- 5μ
Certificates	Slip-resistance	R12 / 67212F
	Flame resistance	M1 / F3
Application	Minimum application temperature	-20°C / -4°F